

... Labeling made easy ...

... GT-12C user terminal with GT-softControl user interface ...

Even more functions, even easier to use, even more possibilities for configuring to the user's needs.

And it still maintains its straightforward structure so the user quickly and intuitively feels at home with all the functionality.



BIZERBA

... closer to your business

Choice of background screen

With the GT-softControl user interface software the screen can be configured by the customer e.g. background color, company logo.

Keys with self-explanatory pictures and pictograms

User soft keys for functions such as basic price, tare or date can be assigned self-explanatory pictures or pictograms. In addition so-called quick buttons can be used to produce operating elements.

Link to the article pictures of a PLU

The user sees immediately which package requires which label and where it has to be attached.

WYSIWYG label previewing

After entering the PLU, the label together with its data is shown on the screen to allow a quick check before printing the label.

... get connected and get ahead ...

Extensive range of applications







SVGA Touch Panel

Mechanics

- Stainless steel housing (Nirosta)
- Front side protection class IP65

Computer

- AMD Geode LX800 CPU board
- 256 MB RAM
- 512 MB Compact Flash

Display

- 12.1" active colour TFT-LCD, resolution 800 x 600 pixels
- Analogue resistive 4-wire touch screen

Interfaces

- 2 x USB 2.0 (1 x USB 2.0 externally available)
- Ethernet 10/100 Base-T

Software

■ Operating system LINUX

General

■ Power supply: 24V DC

GT-softControl

Software

■ Java-based user interface

Betriebssystem

■ runs on Windows XP (on request: Linux, Unix, Solaris or QNX)

Software version

■ runs with instrument software version GLx, CW x 10.0 onwards


Hardware platform

Ilnstallation possible on following hardware platforms: GT-12C, GT-NT, PC

Permission

- This software module may be operated as a calibration display and control unit with the following devices if calibration functionality is required:
 GLP, GLM-L, GLM-I, CWE, GLM-E
- The calibration display of the GT-softControl software cannot be hidden during operation or erased by other software.





Members of the Bizerba Group

Wilhelm-Kraut-Straße 65 72336 Balingen Germany Tel. +49 7433 12-0 Fax +49 7433 12-2696 marketing@bizerba.de www.bizerba.com

Bizerba GmbH & Co. KG

Bizerba House
Eastman Centre
Eastman Way
Hemel Hempstead
Herts HP 2 7 DU
U.K.
Tel. +44 1442 24-0751
Fax +44 1442 2313-28
sales@bizerba.co.uk

Bizerba (U.K.) Limited

Bizerba USA Inc.
31 Gordon Road
Piscataway
New Jersey 08854
USA
Tel. Office +1 732 565-6000
Tel. Service +1 732 565-6001
Fax +1 732 819-0429
us.info@bizerba.com
www.bizerbausa.com

Bizerba Canada Inc. 2810 Argentia Road #9 Mississauga, Ontario L5N 8L2 Canada Tel. +1 905 816-0498 Fax +1 905 816-0497 sales@bizerba.ca www.bizerba.ca

Bizerba South East Asia Pte. Ltd. 1 Fifth Avenue #02-05 Guthrie House Singapore 268802 Singapore Tel. +65 6465-1900 Fax +65 6468-0481 bizerba@bizerba-sea.com

www.bizerba-sea.com