Data Sheet

iS25-Ex



The compact weighing terminal iS25-Ex offers you full functions in Ex zone 1/21. Benefit from reliable and precise results – even in case of time sensitive applications. Fast data transfer and efficient handling ensure smooth processes. An example: The visual tolerance control with LED traffic light function. One of numerous advantages of the easy-to-integrate iS25-Ex.



More information High performance with a wide range of solutions and options.

Product description

Weighing terminal iS25-Ex was specifically designed for simple weighing applications in hazardous areas. As with all our Ex models it is extremely reliable. It meets the demands of your production as safely as the requirements of the ATEX directive in Ex zones 1/21.

The tolerance control integrated by default ensures precise results and can be easily operated: LED lights (red, yellow, green) indicate your staff the weighing results in a fast and clear manner. Tare values can be easily entered via the numeric keypad. Weighing data is directly and safely transferred to higher-ranking systems via interfaces.



Highlights

- Resistant, compact weighing terminal
- Large keys with mechanical pressure point and acoustic feedback ensure trouble-free operation, even with gloves
- Numerous applications: Controlling, order-picking, packaging, shipping, documenting and stock-taking
- Ideal for harsh production environments
- Fast data recording and control
- Efficient cleaning thanks to smooth surfaces and rounded edges
- Meets high hygiene and safety standards
- Flexible weight value units kg / lb or oz
- Integrated applications for efficient weighing and counting processes or for tolerance control
- LED lights for visual tolerance control support
- Metrologically approved data storage
- Integrated service WLAN interface
- 4 inputs / 4 outputs

iS25-Ex



iS25-Fx with stand

Options

- Battery pack with charger and battery Variable lengths of data, control and
- Individual mounting: Table, wall, counter top, stand
- Combinable with different load receptors
- measuring cables
- Column
- Interfaces: Profibus DP, TTY, analog output



iS25-Ex

HD iS25-Ex V2 EN Page 1 / 2

My Bizerba

We offer you solutions from a single source which can be customized and allow you to respond to any change in a flexible manner. Benefit from costs which can be planned and efficient processes. We are happy to advise you.

Bizerba SE & Co. KG

Wilhelm-Kraut-Straße 65 72336 Balingen

T +49 7433 12-0 fax: +49 7433 12-2696 marketing@bizerba.com

www.bizerba.com

HD_iS25-Ex_V2_EN Page 2 / 2